



(Interleaver)

Telcordia GR-1221-CORE

RoHS

-
-
-

- DWDM
- DWDM

- Telcordia GR-1221-CORE
- RoHS

		100GHz~50GHz	200GHz~100GHz
	nm	C-band:1528~1568nm; L-band:1568~1610nm	
	nm	ITU-T Grid	
1	nm	±0.04	
	GHz	±8	±15
2	dB	2.0	2.0
@0.5dB	GHz	≥0.2	≥0.44
@25dB	GHz	≤80	≤160
	dB	≤0.5	
	dB	≤0.5	
	dB	≥25	
	dB	≥40	

		dB	≥50
		dB	≤0.5
		ps	≤0.2
		ps/nm	±75(high chromatic dispersion); ±30(low chromatic dispersion)
			0~65
			-40~+85
		mm	132*35*12
			133*90*16

1. 1dB .
2. .

WINT-□-□-□-□-□-□-□

Application Type: M:MUX D:Demux

Connector 00: no connector FC SC LC/PC APC

Fiber Length 1: 1m customer specify

Fiber Dia. 09: Φ0.9mm 025: Φ0.25mm

Start Channel Number C11 C+11 C12 C+12 C60
C+60...(Refer to ITU channel table)

Channel Spacing 1: 100GHz 3: 50GHz

Band C: C-band L: L-band